PRE-TECH CERTIFICATION 2024.PROTOUR v2/28/24	KART NUMBER	R ENGINE SEAL NUMBER	CHASSIS TAG NUMBER	PIPE SEAL NUMBER	
DRIVER NAME (PLEASE PRINT CLEARLY)	RACE CLA	SS	DATE		
IAME:	CLASS:		DATE:		
DIRECTIONS: PLEASE INDICATE COMPLIAN THIS FORM MUST BE SUBMITTED TO THE SKUSA PRE-GRID (WHETHER THAT BE QUALIFYING, HEAT OR MAIN). FAILU) STEWARD PRI RE TO DO SO M.	OR TO ENTERING THE TR AY RESULT IN A PENALTY	ACK FOR YOUR FIRST CI ASSESSMENT, AS DETE	DMPETITION SESSIOI RMINED BY SKUSA.	
ITEMS THAT NEED TO BE SECURED BY NYLOCK, SAFETY COTTER PINNED, OR SECURED BY CIRCLIP OR SNAP RIN	G:	ERAL AND SAFETY REQU			
STEERING ASSEMBLY	L	_ PUSH BACK BUMPERS REQUIRED FOR ALL CLASSES (EXCEPT SHIFTERS) PER SKUSA RULE SECTION 304			
	Г	CHASSIS TAG PROPERLY	INSTALLED ON DRIVER'S	RIGHT PER SKUSA	
STEERING HUB TO SHAFT BOLT		RULE SECTIONS 252 ANI	0 801		
STEERING SHAFT TO CHASSIS TIE		ENGINE SEAL PROPERLY 253 AND 802/803	INSTALLED PER SKUSA	RULE SECTIONS	
ROD END BOLTS	Г	CAMERA(S) MARKED WI	TH KART # AND MOUNTE	D PER SKUSA	
— KINGPIN BOLTS		RULE SECTION 307.2			
SPINDLE NUT ATTACHING WHEEL		BRAKE FUNCTIONALITY BRAKE PEDAL SHALL RE UNABLE TO TURN	TEST SUFFICIENT FOR(SULT IN ALL APPLICABLE		
BRAKING SYSTEM	Г	CHEST PROTECTORS FO	R APPLICABLE DRIVERS F	ER SKUSA RULE	
PEDAL PIVOT TO CHASSIS	_	106.9			
ACTUATING ROD AND CABLE ENDS		SEAT MOUNTING TABS A		D PER INTENT OF	
MASTER CYLINDER TO CHASSIS BOLTS	Г	CHASSIS MANUFACTURE		м	
CALIPER(S) TO CHASSIS BOLTS		CORRECT KART NUMBER			
PAD RETAINING RODS	L	AS APPROVED IN REGIST			
BRAKE ROTOR TO HUB (METAL LOCK NUTS ONLY)		REAR PROTECTION MEE	IS CURRENT SKUSA RULI	S	
CIK-SPECIFICATION BRAKE SAFETY CABLE WITH A MINIMUM DIAMETER OF 1.8MM		 WEIGHTS/BALLAST & HARDWARE PAINTED WHITE AND LABELED WITH KART #. SEE RULE SECTION 302.1.4 WEIGHT(S) UNDER 7 LBS. SECURED BY (1) 5/16" / 8MM BOLT 			
BODYWORK		• WEIGHT(S) 7+ LBS. SEC	CURED BY TWO (2) 5/16" ,	' 8MM BOLTS	
BODYWORK MOUNTED AS INTENDED BY MANUFACTU	RER	DOUBLE NUTTED OR DRILLED WITH BOLT SAFETY-WIRED OR COTTER PINNED		'Y-WIRED OR	
MAXIMUM LENGTH AND WIDTH PER SKUSA RULEBOD	к	STARTER BATTERIES LAI	BELED WITH KART # AND CLUDING 175-LB TIE WRA		
SPEC FUEL & TIRES	Г	AUXILIARY THROTTLE CA	ABLE RETURN SPRING (AI	L CLASSES]	
SPEC FUEL: SUNOCO 112 // SPEC OIL: ELF HTX909 MANDATORY RATIO: 1 GAL FUEL TO 6.76 OZ OIL	Г	HELMET AND SUIT MEET	LATEST SKUSA RULES.		
SPEC TIRES: EVINCO SK-M MED (SHIFTERS & PRO X3 NEW EVINCO SK-H2 HARD (ALL OTHER CLASSES)	 []	MANDATORY: ENTER TH YOUR HELMET HERE:	E HELMET RATING FROM	THE INSIDE OF	
EVENT RACE TIRES – ENTER BAR CODE NU	JMBERS	SEMI PRO: FILL BO	XES 1 -4 // PRO: F	ILL BOXES 1-8	
01 02	0	3	04		

05	06	07	08			
SIGNED BY:		PLEASE PRINT THE NA	PLEASE PRINT THE NAME OF THE SIGNER:			

BY SIGNING / FILLING OUT THIS FORM - I PRESENT THIS KART AND DOCUMENT AND CERTIFY THAT ALL ITEMS ON THIS FORM HAVE BEEN COMPLETED, VERIFIED, AND WILL BE MAINTAINED THROUGHOUT THE DURATION OF THE EVENT. ACCURACY OF THIS DOCUMENT IS 100% THE RESPONSIBILITY OF THE COMPETITOR. INACCURATE INFORMATION COULD RESULT IN DISQUALIFICATION OR PENALTY.