



PRE-TECH CERTIFICATION

2021-PRO TOUR

v051221

KART NUMBER:

ENGINE SEAL NUMBER:

CHASSIS TAG NUMBER:

DATE:

DRIVER NAME AND RACE CLASS (PLEASE PRINT):

DRIVER NAME:

RACE CLASS:

DIRECTIONS: PLEASE INDICATE COMPLIANCE FOR EACH ITEM BY CHECKING THE CORRESPONDING BOX. THIS FORM MUST BE SUBMITTED TO THE SKUSA PRE-GRID STEWARD PRIOR TO ENTERING THE TRACK FOR YOUR FIRST COMPETITION SESSION (WHETHER THAT BE QUALIFYING, HEAT OR MAIN). FAILURE TO DO SO MAY RESULT IN A PENALTY ASSESSMENT, AS DETERMINED BY SKUSA.

ITEMS THAT NEED TO BE SECURED BY NYLOCK, SAFETY WIRE, COTTER PINNED, OR SECURED BY CIRCLIP OR SNAP RING:

STEERING ASSEMBLY

- STEERING WHEEL TO HUB BOLTS
- STEERING HUB TO SHAFT BOLT
- STEERING SHAFT TO CHASSIS
- TIE ROD END BOLTS
- KINGPIN BOLTS
- SPINDLE NUT ATTACHING WHEEL

BRAKING SYSTEM

- PEDAL PIVOT TO CHASSIS
- ACTUATING ROD AND CABLE ENDS
- MASTER CYLINDER TO CHASSIS BOLTS
- CALIPER(S) TO CHASSIS BOLTS
- PAD RETAINING RODS
- BRAKE ROTOR TO HUB
(METAL LOCKNUTS ONLY)

BODYWORK

- BODYWORK MOUNTED AS INTENDED BY MANUFACTURER
- MAXIMUM LENGTH AND WIDTH PER SKUSA RULEBOOK

FUEL (ALL CLASSES)

- SPEC FUEL: VP MS98
SPEC OIL: ELF HTX 909 SAE 50
- MANDATORY RATIO: 1 GAL FUEL TO 6.76 OZ OIL

EVENT RACE TIRES -- ENTER BAR CODE NUMBERS

01 02 03 04

SIGNED BY:

PLEASE PRINT THE NAME OF THE SIGNER:

GENERAL SAFETY REQUIREMENTS WHICH MUST BE ADHERED TO:

- PUSH BACK BUMPER BRACKETS IN PLACE AND READY FOR BUMPER INSPECTION AND INSTALLATION AT GRID (ALL CLASSES) - 27MM MINIMUM CLEARANCE ON UPPER BUMPER BAR
- CIK-SPECIFICATION BRAKE SAFETY CABLE WITH A MINIMUM DIAMETER OF 1.8MM
- BRAKE FUNCTIONALITY TEST - SUFFICIENT FORCE APPLIED TO BRAKE PEDAL SHALL RESULT IN ALL APPLICABLE WHEELS BEING UNABLE TO TURN
- HELMET AND SUIT MEETS LATEST SKUSA RULES. PLEASE ENTER THE HELMET RATING FROM THE INSIDE OF YOUR HELMET HERE:
- SEAT MOUNTING TABS AND STRUTS IMPLEMENTED PER INTENT OF CHASSIS MANUFACTURER
- FUNCTIONAL FUEL AND WATER RECOVERY SYSTEM
- CORRECT KART NUMBER, COLOR AND BACKGROUND (4 LOCATIONS) AS APPROVED IN REGISTRATION
- REAR PROTECTION MEETS CURRENT SKUSA RULES
- WEIGHT(S) (BALLAST) -- AND HARDWARE -- PAINTED WHITE
 - WEIGHT(S) UNDER 7 LBS. SECURED BY (1) 5/16" / 8MM BOLT
 - WEIGHT(S) 7+ LBS. SECURED BY TWO (2) 5/16" / 8MM BOLTS
 - DOUBLE NUTTED OR DRILLED WITH BOLT SAFETY-WIRED OR COTTER PINNED
- RECOMMENDED: METAL SEAT/SEAT STRUT REINFORCEMENT WASHERS - MIN 35MM DIAMETER
- STARTER BATTERIES LABELED WITH KART # AND CLASS, AND MOUNTED PER SKUSA RULE 20.3.4.3. NOTE: 175-LB TIE WRAPS ARE REQUIRED, PER RULE 20.3.4.3.1.
- AUXILIARY THROTTLE CABLE RETURN SPRING (ALL CLASSES)

BY SIGNING / FILLING THIS FORM OUT — I PRESENT THIS KART AND DOCUMENT AND CERTIFY THAT ALL ITEMS ON THIS FORM HAVE BEEN COMPLETED, VERIFIED, AND WILL BE MAINTAINED THROUGHOUT THE DURATION OF THE EVENT. ACCURACY OF THIS DOCUMENT IS 100% THE RESPONSIBILITY OF THE COMPETITOR. INACCURATE INFORMATION COULD RESULT IN DISQUALIFICATION OR PENALTY.